



SLATE LITE

the future of stone.



DATA SHEET: SLATE-LITE SPECIAL IMPREGNATION

PRODUCT DESCRIPTION

SLATE-LITE SPECIAL IMPREGNATION is a water-dissolved impregnating agent. It is solvent-free, ready to use and contains highly effective oil and water repellent polymers and additives.

SLATE-LITE SPECIAL IMPREGNATION penetrates the absorbent, porous surface and immediately forms an ultra-thin, invisible film in the capillaries. This reduces absorbency and thus largely prevents water, oil and grease from penetrating and causing stains. Soiling therefore remains on the surface, where it can be easily wiped off. The appearance of the treated surface usually changes little or not at all.

APPLICATION

SLATE-LITE SPECIAL IMPREGNATION can be applied to all *Slate-Lite* surfaces that have been finished on the wall and have low traffic.

INSTRUCTIONS FOR USE

The surface to be applied must be clean, dry and free of coatings. Apply the impregnation with a short haired roller on the entire surface to ensure a gapless application. After 30 min, wipe off possible residues with a dry cloth. Do not apply too much pressure during application, otherwise blistering may occur. Repeat 3-4 times to reinforce protection. Renew every 3-4 years.

Before starting the work, it is recommended to make a sample area of 1-2m² to check the effectiveness of the impregnation, to assess the appearance of the treated object (color tone deepening) and to determine the material consumption with sufficient accuracy.

TECHNICAL DATA

YIELD: approx. 30 m² / 322,9 ft² (with 2-fold application)
PH-VALUE: approx. 4.5
WORKING TEMPERATURE: +10°C / 50°F to +25 °C / 77°F
COLOR: clear, yellowish, thin liquid
ODOR: almost odorless
DRYING TIME: approx. 20-30 min per application
Full effect only after 48h, do not allow to come into contact with water or oil beforehand.
DENSITY: approx. 1.0 g/cm³

FLASH POINT: approx. 36 °C / 96,8°F
STORAGE: Store closed, frost-free and cool.
Can be stored for up to 3 years.